IPC ASSOCIATION CO ELECTRONICS IN	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both lev	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfc Information			
upplier Ir	nformation													
Company nar	me*	Company unique ID			U	Unique ID Authority				Response Date*				
nsemi											2023-06-08			
Contact Nam	e	Title - Contact			P	Phone - Contact*				Email - Contact*				
Product-Env	y-Stewards		Product Enviro Compliance			N	NA				Product-Env-Stewards@onsemi.com			
uthorized R	Representative*	Title - Representative			P	Phone - Representative*			Email - Representative*					
Product-Env	y-Stewards	Product Enviro Compliance			N	NA				Product-Env-Stewards@onsemi.com				
Ro	equester Item Number	Mfr Item	Number	Mfr Item Name]	Effective Date	Version	N	Manufacturing Site	W	eight*	UOM	Unit Type
		NCP1937C61DR2G COMBO PFC & QUAZ		UAZI FLYBACI	K 2	2023-06-08		P	PH1		56.78	mg	Each	
Ianufactu	uring Proccess Informa	ation												
Te	Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-02			STD-020 MSL R	Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle						eles			
Matte Tin (Sn) - annealed CU Allo			CU Alloy	1			260		C	30	second	s 3		
omments														
vel 1 - maxi	mum time at peak temperat	ture during sol	ldering is 10-3	30 seconds										
or more info	ormation regarding materia	l composition	please refer to	page 3										

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier neter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided in formation the Supplier's Standard Terms andConditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material Weight Unit of M		Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.32	mg	Supplier	Silicon (Si)	7440-21-3		1.32	mg
Die Attach	0.48	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.096	mg
			Supplier	Silver (Ag)	7440-22-4		0.384	mg
Lead Frame	36.06		Supplier	Silver (Ag)	7440-22-4		0.0288	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0433	mg
			Supplier	Iron (Fe)	7439-89-6		0.8474	mg
			Supplier	Copper (Cu)	7440-50-8		35.1297	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0108	mg
Mold Compound-Black	125.7	mg		Epoxy Phenol Resin	proprietary data		13.1985	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		112.5015	mg
Plating	2.75	mg	Supplier	Tin (Sn)	7440-31-5		2.75	mg
Wire Bond - Au	0.47	mg	Supplier	Gold (Au)	7440-57-5	_	0.47	mg