



PCN / EOL Notification

PCN Number: CC135103A (Revised 2/13/14) Notification Date*: December 27, 2013
See Changes in Blue Text

Title: 2-Kbit Two-wire Interface Industrial Temperature Grade (-40C to 85C) Serial EEPROM (AT24C02C) Layout Optimization and Device Enhancement		
Product Identification: All Packages of the Industrial Temperature Grade (-40C to +85C) AT24C02C		
Reason for Change:	<input checked="" type="checkbox"/> Material / Composition <input type="checkbox"/> Processing / Manufacturing <input checked="" type="checkbox"/> Design / Firmware <input type="checkbox"/> Datasheet	<input type="checkbox"/> Manufacturing Location <input type="checkbox"/> Quality / Reliability <input type="checkbox"/> Logistics <input type="checkbox"/> Other:
Change Description: Atmel has optimized the layout of the Serial EEPROM Industrial Temperature Grade (-40C to +85C) AT24C02C device (Two-wire interface, 2-Kbit density). The catalog part number AT24C02C will be replaced by AT 24C02D (see Table 2). The new devices are pin-to-pin and functionally backward compatible with the current AT24C02C devices with the following exceptions and enhancements. <u>Supply Voltage (V_{CC}) Range</u> With a growing number of MCUs, SoCs, and ASICs migrating to lower supply voltages as a result of process lithography reductions, and as the electronics industry in general also moves to lower supply voltages to reduce power consumption, Atmel developed the next-generation AT24C02D to enhance performance for these lower voltage requirements. Unlike the AT24C02C devices that operate over a 1.7V to 5.5V voltage range, the AT24C02D devices have been designed to operate from a 1.7V to 3.6V supply. As a result, the AT24C02D has significant improvements and advantages over the AT24C02C devices with respect to power consumption, endurance, and noise suppression (see Table 1 for all differences). <i>Please contact Atmel (MemoryPCN@atmel.com) for details regarding continued availability of AT24C02C devices for applications operating at voltage levels above 3.6V.</i> <u>Copper (Cu) bond wire usage</u> In order to increase manufacturing flexibility and to ensure a long-term continuity of supply, Atmel will manufacture (SOIC, TSSOP, SOT23 and UDFN) packages using copper bond (Cu) wire.		

Table 1

Parameter/Feature	AT24C02C	AT24C02D
Operating Voltage	1.7V to 5.5V	1.7V to 3.6V
Operating Temperature	-40°C to +85°C	-40°C to +85°C
Endurance	1,000,000 cycles (Page Mode, +25°C, 3.3V)	1,000,000 cycles (Byte or Page Mode, +25°C, 1.7V to 3.6V)
Data Retention	100 years	100 years
Supply Current, Read	0.4mA typ (5.0V, 400kHz) 1.0mA max (5.0V, 400kHz)	0.08mA typ (1.8V, 400kHz) 0.3mA max (1.8V, 400kHz) 0.15mA typ (3.6V, 1MHz) 0.5mA max (3.6V, 1MHz)
Supply Current, Write	2.0mA typ (5.0V, 400kHz) 3.0mA max (5.0V, 400kHz)	0.2mA typ (3.6V, 1MHz) 1.0mA max (3.6V, 1MHz)
Standby Current	1µA max (1.7V) 6µA max (5.5V)	0.08µA typ (1.8V) 0.4µA max (1.8V) 0.1µA typ (3.6V) 0.8µA max (3.6V)
Maximum Clock Frequency	1MHz (2.5V min.) 400kHz (1.7V min.)	1MHz (2.5V min.) 400kHz (1.7V min.)
Clock Pulse Width Low	1.2µs min (fSCL = 400kHz) 0.4µs min (fSCL = 1MHz)	1.3µs min (fSCL = 400kHz) 0.5µs min (fSCL = 1MHz)
Clock Pulse Width High	0.6µs min (fSCL = 400kHz) 0.4µs min (fSCL = 1MHz)	0.6µs min (fSCL = 400kHz) 0.4µs min (fSCL = 1MHz)
Input Filter Noise Suppression	100ns max (fSCL = 400kHz) 50ns max (fSCL = 1MHz)	100ns max (fSCL = 400kHz) 100ns max (fSCL = 1MHz)
Clock Low to Data Out Valid	900ns max (fSCL = 400kHz) 550ns max (fSCL = 1MHz)	900ns max (fSCL = 400kHz) 450ns max (fSCL = 1MHz)
Bus Free Time Between Start and Stop	1.2µs min (fSCL = 400kHz) 0.5µs min (fSCL = 1MHz)	1.3µs min (fSCL = 400kHz) 0.5µs min (fSCL = 1MHz)
Input Rise Time	300ns max (fSCL = 400kHz) 300ns max (fSCL = 1MHz)	300ns max (fSCL = 400kHz) 100ns max (fSCL = 1MHz)
Input Fall Time	300ns max (fSCL = 400kHz) 100ns max (fSCL = 1MHz)	300ns max (fSCL = 400kHz) 100ns max (fSCL = 1MHz)
Write Cycle Time	5ms max	5ms max
Page Write Size	8 bytes max	8 bytes max
Full Array Hardware Write Protect	Yes	Yes

Identification Method to Distinguish Change:

NEW catalog part numbers of AT24C02C changes to AT**24C02D**. Please refer to datasheet for part marking schemes for each package type.

Table 2

This is the listing for standard datasheet offering, PCN also applies to all (customer specific) special CAN part numbers that are not listed in the table below:

EOL Part Number	Replace Part Number	Package	Carrier Type
AT24C02C-PUM	AT24C02D-PUM	PDIP	Bulk
AT24C02C-SSHM-B	AT24C02D-SSHM-B	JEDEC SOIC	Bulk
AT24C02C-SSHM-T	AT24C02D-SSHM-T	JEDEC SOIC	T/R, 4K per reel
AT24C02C-XHM-B	AT24C02D-XHM-B	TSSOP	Bulk
AT24C02C-XHM-T	AT24C02D-XHM-T	TSSOP	T/R, 5K per reel
AT24C02C-MAHM-T	AT24C02D-MAHM-T	UDFN	T/R, 5K per reel
AT24C02C-STUM-T	AT24C02D-STUM-T	SOT23	T/R, 5K per reel
AT24C02C-CUM-T	AT24C02D-CUM-T	VFBGA	T/R, 5K per reel
AT24C02C-WWU11M	AT24C02D-WWU11M	Wafer Sales	
AT24C02C-WWU27M	AT24C02D-WWU27M	Wafer Sales	

Qualification Data: Available Will be available:
(mm/dd/yr): Not Applicable**Samples:** Available Will be available
(mm/dd/yr): Not Applicable**Quantifiable Impact on Quality & Reliability:**

No impact. Form, fit, and function [over the 1.7V to 3.6V range](#) remains unchanged.

Forecasted Availability Date: December 2013

Last Time Buy Date: June 20, 2014

Last Ship Date: December 20, 2014

**All orders placed after the notification date are non-cancellable and non-returnable (NCNR).*

Atmel Contact: Please contact your Atmel Sales Representative or Distributor for additional information (when replying via e-mail please include the PCN number in subject line).

Information provided herein is in connection with Atmel products and this information is provided "AS IS". Atmel assumes no responsibility for any errors that may appear in this document. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

Attention Distributors: Product(s) identified in this notification will become obsolete and as such this EOL notification will act as the official written notification. All obsolete products will be listed in the next published quarterly distributor price book, following an PCN/EOL change, and listed on the obsolescence form which accompanies said price book. Within thirty (30) days from the published date of the price book, Distributor shall notify Atmel in writing of Distributor's then current inventory of the obsolete product

CUSTOMER ACKNOWLEDGEMENT OF RECEIPT: Atmel requests you acknowledge receipt of this PCN / EOL. Please complete and email to pcnadm@atmel.com and the Atmel Contact listed above. In your acknowledgement, you can grant approval or request additional information. **Atmel will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice.**

To be completed by customer:

Approved

Rejected (Please state reason for rejection):

Company:
Name:
Title:
Date:
Email
Address:
Location:
Comments: