

LINEAR TECHNOLOGY MATERIALS DECLARATION

1t3492ife#pbf

(Engineering Calculation)

TSSOP Exp. Pad

(printed on: 2020-07-11 20:29:50)

TOTAL MASS (g) : 0.095298

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.003154 | 1000000 | 33096.0585938 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.030596 | 975000 | 321054.84375 | | |
| | | Iron (Fe) | 7439-89-6 | 0.000753 | 24000 | 7901.5 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000009 | 300 | 94.440246582 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000022 | 700 | 230.853927612 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.031380 | 1000000 | 329281.65625 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.002480 | 1000000 | 26027.2480469 | | |
| | | External Plating Total: | | | | 0.002480 | 1000000 | 26027.2480469 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000806 | 1000000 | 8457.6484375 | | |
| Internal Plating Total: | | | | 0.000806 | 1000000 | 8457.6484375 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.000958 | 750000 | 10052.6386719 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000319 | 250000 | 3347.38208008 | | |
| Die Attach Total: | | | | 0.001277 | 1000000 | 13400.0205078 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.007460 | 135000 | 78280.46875 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.047524 | 860000 | 498686.46875 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000276 | 5000 | 2896.16748047 | | |
| | | Encapsulation Total: | | | | 0.055260 | 1000000 | 579863.0625 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000941 | 1000000 | 9874.25195312 | | |
| | | | | | TOTAL MASS (g) : | 0.095298 | | |